



DISPENSING SOLUTIONS

PROGRESS > RETAIL LINE

Add value to your business.



PRODUCT LINE

Fuel dispensers of Progress Retail Line have an elegant and compact design, adding a clean look and an extra appeal to the forecourt. Made with the finest materials and a superior construction quality, they represent the perfect choice for those who are looking for performance, robustness and reliability.

All Retail Line models offer great performance, flexibility, robustness, reliability, cost effectiveness and a great user experience to your customers.

All models allow an almost effortless access to all parts, ensuring an easy maintenance and upgrade capabilities that are key to your business.

Large image panels and an uncluttered hydraulic cabinet offer plenty of space for a continuous branding across the forecourt.

All models from the Progress Retail Line can be further tailored to your needs by upgrading your fuel dispenser with multimedia, payment terminals, vapour recovering, monitoring and ATC. Most options can be installed at a later stage, according to your business requirements and growth.

The Progress Retail Line offers flexible range of dispensers that can be tailored to all your business requirements, from one to ten hoses, five different products, a flow rate of up to 200 L/min, payment systems and multimedia.



P1000R

With the smallest footprint of the family, the P1000R is the entry-level model of the Progress range. With one fuel grid, one or two hoses and a dispensing capacity of up to 130 L/min, it uses the same core technologies as the premium retail dispenser range. It is the right choice for those who are looking for basic features with a great performance.



P2000

The P2000 is a very flexible dispenser. With a small footprint, up to two fuel grids, one or two hoses and a dispensing capacity of up to 200 L/min, it uses the same core technologies as the premium retail dispenser range. The P2000 is the right choice for those who are looking for an enhanced dispenser that offers higher flow rate options, while ensuring a small footprint.



P3000

The P3000 has the same main features, footprint and form factor as the P2000, with one or two fuel grids, up to four hose options, lane-oriented hoses/nozzles and able to achieve a flow rate of up to 130 L/min. The P3000 is the right choice for those who have limited space in their forecourt and need an enhanced, flexible and compact dispenser.



P4000C

This is the H-style multiproduct model from the Progress family, with two hose options (hanging hose and hose retraction), up to four fuel grids and eight hoses, and a dispensing capacity of up to 130L/min. This model also allows the integration of multimedia and payment systems. This is the perfect choice for those who are looking for a more compact multiproduct dispenser with a great performance, easy to fit any forecourt.



P5000HH

The hanging-hose model from the Progress Retail Line offers the best ratio between maintenance cost per hose, protection and uncluttered access to the dispenser, ensuring a smooth user experience. It can have up to four fuel grids, eight hoses and a maximum flow rate of 130L/min. Multimedia and payment systems are also available. A great choice for those who privilege a great design, reliability, performance and low maintenance cost.



P5000LH

This is the most customizable dispenser in the Progress range. It can have up to five fuel grids and ten hoses, combined with alternative products, like LPG and AdBlue (with heating). It can provide flow rates of up to 130L/min. The elastic hose retraction system allows an easy handling and ensures the best possible user experience. All media/ payment system options are available. It represents the perfect choice for those who are looking for an adaptable dispenser that can keep up with the challenges of their business.

> RETAIL LINE

COMPARISON CHART		P1000R	P2000	P3000	P4000C	P5000HH	P5000LH
Features	Max. No. Sides	2	2	2	2	2	2
	Max. No. Displays/Side	1	2	2	2	1	1
	Max. No. Filling Points	1	2	2	2	2	2
	Max No. Products	1	2	2	4	4	5
	Max No. Hoses	2	2	4	8	8	10
	Electronic Calibration	*	*	*	*	*	*
	Lane-Oriented Hoses/Nozzles	x	x	*	*	*	*
	Island-Oriented Hoses/Nozzles	*	*	x	x	x	x
	Price/Volume Display	*	*	*	*	*	*
Admission	Suction	*	*	*	*	*	*
	Pressure	*	*	*	*	*	*
Hose Hanging	Standard Hose Bracket	*	*	x	x	x	x
	Hose Retraction	x	x	x	*	x	*
	Hanging Hose	x	x	x	*	*	x
	Hose Mast	*	*	*	x	x	x
Flow Rate (L/min)	10	*	*	*	*	*	*
	40	*	*	*	*	*	*
	80	*	*	*	*	*	*
	130	*	*	*	*	*	*
	160	x	*	x	x	x	x
	200	x	*	x	x	x	x
Products	Petrol	*	*	*	*	*	*
	Diesel	*	*	*	*	*	*
	Biodiesel	*	*	*	*	*	*
	Biodiesel Blends	*	*	*	*	*	*
	Ethanol [E85] (4)	*	*	*	*	*	*
	LPG (4)	x	*	x	x	x	*
	Adblue (4)	*	*(1)	*(1)	*(1)	*(1)	*
	Speed Selector (40/80 L/min)	*	*	*	*	*	*
Electronic Options	Voice Module	x	*	*	*	*	*
	Electro-mechanical Totalizers	*	*	*	*	*	*
	Unit Price Display	x	x	x	*	*	*
	Volume Preset	*	*	*	*	*	*
	Amount Preset	*	*	*	*	*	*
	Circuit Breaker	*	*	*	*	*	*
	Main Safety Switch (LPG)	x	*	x	x	x	*
	Electronics Head Heating	*	*	*	*	*	*
	Vapour Recovery Stage II	*(2)	*	*	*	*	*

COMPARISON CHART		P1000R	P2000	P3000	P4000C	P5000HH	P5000LH	
Electronic Options	Vapour Recovery w/Monitoring	*(2)	*	*	*	*	*	
	Automatic Temperature Compensation	*	*	*	*	*	*	
	Single-Phase Motor	*	*	*	*	*	*	
	Three-Phase Motor	*	*	*	*	*	*	
	TAGs	x	x	x	*	*	*	
	OPT (3)	x	x	x	*	*	*	
	Multimedia	x	x	x	*	*	*	
	Hydraulic Options	Adblue Hydraulic Housing Heating (ATEX)	*	x	x	x	x	*
		Adblue Hydraulic Housing Heating	*	x	x	x	x	*
Low Temperature Kit		*	*	*	*	*	*	
Satellite Ready		*	*	*	*	*	*	
Breakaway Couplings		*	*	*	*	*	*	
Custom Nozzles and Sleeves		*	*	*	*	*	*	
Flexible Riser Connection		*	*	*	*	*	*	
Structure Options		Stainless Steel AISI304 Image Panel	*	*	*	*	*	*
	Stainless Steel AISI316	*	*	*	*	*	*	
	Foundation Frame	*	*	*	*	*	*	
	Custom Corporative Image	*	*	*	*	*	*	
	Lifting Solution	x	x	x	*	*	*	
Multiple Communication Protocols/Interfaces are available. For more details please refer to the correspondent product datasheet.								
Notes: (*) Available; (x) Not Available; *(1) Without heating; *(2) Only available with suction pumps; *(3) Integration with wide range of terminals; *(4) Only available with pressure version.								
Environmental Conditions								
Environment classes: M2 / E1								
Temperature Range Liquid: -10°C / +50°C								
Temperature Range Ambient: -25°C / +55°C								

© 2018 Petrotec Group | All rights reserved. Petrotec, the Petrotec logo, Progress and combinations thereof are registered trademarks of Petrotec Group. Other names are informational and may be trademarks of their respective owners. Petrotec is continuously improving its products. Changes on the specifications may occur without prior notice. The imagery used may be indicative of style only. The available brochures are a guide and do not constitute an offer or contract.

